

# 

# **CX1 Connect USB Audio Interface**

# **User Guide**



# **CX1 Connect USB Audio Interface**

### Introduction

Record at home or on the go with the CAD Audio CX1 USB Audio Interface. The CX1 features an XLR combo input which can accommodate microphones using XLR connectors or line level devices using 1/4" connectors. The CX1 is an easy to use and affordable interface ideal for recording your next vocal track, podcast, voice over project or acoustic instrument track. The CX1 offers 48V phantom power and is fully USB powered, no external power source required. You'll get high-quality professional recordings with 24-bit/96kHz digital resolution, all in a lightweight, compact device that is easy to take with you for portable recording.

The CX1 contains the following features:

- · Value-packed single channel USB audio interface for home or mobile recording
- Record at professional-level 24-bit/96kHz resolution
- Includes +48V phantom power for use with studio condenser microphones
- · USB bus powered
- Compatible with nearly any recording software on Windows® or Macintosh® operating systems
- 2 vear warranty





# Controls

computer via USB.

- 1. INPUT connect a microphone using XLR connector, or a line level device using 1/4" (6.35mm) connector.
- 2. GAIN This knob controls the gain (amplification factor) for
- 3. Headphone output Connect your monitor headphones here This is a 1/4" (6.35mm) TRS (tip-ring-sleeve) stereo jack.
- 4. MONITOR This knob controls headphone monitor volume.
- 5. +48V This light indicates that 48V phantom power is present at the XLR input connectors.
- 6. POWER This light indicates that Connect II is being powered by USB.
- 7. LINE OUTPUTS These are the left and right line-level signal outputs. These jacks accept RCA-type plugs 8. USB 2.0 Type-C connector. Use this to connect to your
- 9. +48V This switch enables +48V phantom power at the XLR input connectors.

### Specifications ... 20Hz-20kHz Frequency Response ..... Resolution/Sample Rate ... 24Bit/96kHz Phantom Power ... ....+48V Dvnamic Range .. ... 118dB (A-weighted) ..... -110dBu (A-weighted) Max Input Level Mic.. .+8dBu ....+19dBu Input Impedance .. 3k Ω 20k O Line Gain Range ...50dB Weight 0.33lbs (0.15kg) Dimensions ....5.1" x 4.2" x 1.5" (13cm x 10.7cm x 3.7cm)

# Applications





# Computer Interface

Step 1: Connect this product with computer via USB cable Step 2: Computer open device manager Step 3: The selected "Sound, video and game controllers" shows

the device name: "CAD Audio CX1 Interface" of the product



## Macintosh®:


Step 1: Open the Mac OS System Preferences.

Step 2: Select "Sound", then "Input". Step 3: Select the device "CAD Audio CX1 Interface" for sound

tout where & Market 2 2 3 4 2 2 2 3 4 5 4 5 4 5 6 5

# Macintosh®:

When you need to monitor through this product, open the Mac OS System Preferences, select "Sound", then "Output". Select the device "CAD Audio CX1 Interface" for sound output.



## Two-Year Limited Warranty

CAD Audio hereby warrants that this product will be free of defects in material and workmanship for a period of two years from the date of purchase. In the unlikely event that a defect occurs, CAD will, at its option, either repair or replace with a new unit of equal or greater value. In the event that a suitable replacement is unavailable, CAD Audio may elect to reimburse owner for the cost of local repairs or issue a refund in the amount of the original purchase price. Items must be purchased from an authorized CAD Audio dealer, and the warrantly is not transferable from the original owner. Please retain proof of purchase to validate the purchase deta and include it with any warranty dain. ream proor op purchase to validate the purchase date and include it win any warranty claim. This warranty excludes exterior his not appearance, damage from abuse, misuse of the product, use contrary to CAD is instructions or unauthorized repair. All implied warranties, merchantability, or fifness for a particular purpose is hereby dicidatimed and CAD hereby disclaims liability for indicidental, special or consequential diamages resulting from the use or unavailability of this product. This warranty gives you specific legal rights and you may have other rights that vary from state to state. Some states do not allow the exclusion or limitation of incidental or consequential damages or state. Some states do not allow the exclusion or limitation of incidental or consequential damages or state. Some states do not allow the exclusion or limitation of incidental or consequential damages or state. Some states do not allow the exclusion or limitation of understance or consequential damages or state. Some states do not allow the exclusion or limitation or such as the state.

Note: No other warranty, written or oral is authorized by CAD Audio.

- Note: No other warranty, written or oral is authorized by CAU Audio.

  To initiate a warranty claim, please contact American Music and Sound at 1-800-431-2609 to obtain a return authorization number and shipping instructions.

  A return authorization is required for all returns, RETURNS WITHOUT A PRE-APPROVED RETURN AUTHORIZATION NUMBER WILL BE REFUSED.
- Please use at least 3 inches of padding surrounding the product for
- Prease use at reast 3 mores or packing strictlining the product of protection during shipment. Retain your tracking number until your warranty claim has been resolved. We recommend using an insured shipping method in case of loss.
- or damage during shipment

If outside the United States, contact your local dealer or distributor for warranty details.

6573 Cochran Rd., Bldg. I Solon, OH 44139 U.S.A. Tel: (440) 349-4900 Fax: (440) 248-4904 Sales: 800-762-9266 cadaudio.com

Distributed Worldwide by American Music and Sound 925 Broadbeck Drive, Suite 220 Newbury Park, CA 91320 U.S.A. Tel: (800) 431-2609 Fax: (800) 431-3129

©2023 CAD Audio Rev00 3-23

